



Product Information



FDi Part Number: FD-020-244



Technology: 2 Wire



Encryption : BLE, DESFire, MIFARE® Classic, MIFARE® Plus

DESCRIPTION

The Titanium P40 proximity reader is a 2-SMART key reader developed for the scalable iPassan access controller. This 2-SMART reader is based on our own protocol and offers exclusive features and security.

With its up-to-the-minute design, it can be easily integrated in your commercial and residential projects. In addition to Mifare® RFID technology, this reader offers the opportunity to work with Bluetooth virtual credentials.

KEY CHARACTERISTICS

- High security and easy installation with the 2-wire output and encrypted bus
- Mifare® Classic and Mifare® Plus proximity reader (AES 128 bit encryption)
- Secure Bluetooth read technology for access with virtual credentials
- Integrated LEDs
- Surface-mounted with terminal output – IP65 (provided installation instructions are complied with)
- Firmware updated online and remotely

Power supply

The P40 RFID reader draws its power supply from the FDI access controller.

Communication

The 2-SMART proximity reader is connected via 2 wires and two-way communicates permanently (FDI protocol) with the iPassan access controller LPU. The controller is real-time aware if the reader is connected. The controller is real-time aware if the reader is connected.

Updating firmware

P40 key reader firmware can be updated via iPassan Manager software.

TECHNICAL CHARACTERISTICS

Power supply

Operating voltage: 12V supplied by the controller via the 2 wires

Outputs

- 2-SMART output: 2 wire
- Max. cable length: 100 m – 8/10 AWG20
- Frequency: 13.56 MHz (Mifare® Classic, Mifare® Plus and DESFire) + Bluetooth Low Energy (BLE)

Read distance

- Mifare® Classic: Up to 40 mm
- BLE : based on mode and settings

LEDs

- 3 colors
- Managed via the controller software

Temperature

- Operating temperature: -20°C to 60°C
- Storage temperature: -20°C to 70°C
- Humidity : 85 RH max.

PROTECTION RATING

- Protection rating: IK10
- Waterproof rating: IP65

Size

- Size (L x l x H): 90 mm x 47 mm x 23 mm
- Weight: 65g